



Conventional Vertical Milling Machines

MF 1 VP



PRODUCT.BROCHURE.SKU: 301215

The multi-purpose milling machine series MF1 impresses with its design and is indispensable in many repair workshops as well as training and production departments. The X-axis is steplessly adjustable with a feed device and the swiveling vertical milling head with a wide steplessly adjustable speed range processes steel up to non-ferrous metals. The standard accessories include an automatic quill feed and pneumatic tool clamping as well as a mounted position indicator.

- Swiveling, tiltable cutter head with quill feed
- Pneumatic tool tightening system
- Infinitely variable spindle speed
- Feed on X-axis with rapid feed
- Extensive standard equipment

PRODUCT.BROCHURE.technical_specs

ATTRIBUTES.MEG-000008.DESCRPTION

attributes.MEG-000008.MER-000271	1245 mm x 230 mm
attributes.MEG-000008.MER-000020	3 positions
attributes.MEG-000008.MER-002446	16 mm x 63.5 mm

ATTRIBUTES.MEG-000059.DESCRPTION

attributes.MEG-000059.MER-000287	760 mm
attributes.MEG-000059.MER-000288	290 mm
attributes.MEG-000059.MER-000289	370 mm

ATTRIBUTES.MEG-000012.DESCRPTION

attributes.MEG-000012.MER-001501	60 1/min - 4200 1/min
attributes.MEG-000012.MER-000920	127 mm
attributes.MEG-000012.MER-000942	SK 30 DIN 2080
attributes.MEG-000012.MER-000451	171 mm - 476 mm

ATTRIBUTES.MEG-000006.DESCRPTION

attributes.MEG-000006.MER-000298	19 mm/min - 890 mm/min
attributes.MEG-000006.MER-000463	(3) 0,04;0,08;0,13 mm/R
attributes.MEG-000006.MER-001560	370 mm

ATTRIBUTES.MEG-000002.DESCRPTION

attributes.MEG-000002.MER-000159	2.25 kW
----------------------------------	---------

ATTRIBUTES.MEG-000004.DESCRPTION

attributes.MEG-000004.MER-000002-height	2.05 m x 1.63 m x 2.07 m
attributes.MEG-000004.MER-000108	950 kg



PRODUCT.BROCHURE.PRODUCT_DETAILS

- The most widely used milling machine type in the world - with standard pneumatic tool clamping
- Infinitely variable spindle speed via hand wheel adjustment
- Larger table with larger travel on X
- TV 1000 automatic table advance on X-axis is included, retrofitting of Y-axis available
- Head swivels on 3 axes: swivel r + l $\pm 90^\circ$; tilt forward + reverse $\pm 45^\circ$; rotation on the column $\pm 45^\circ$
- Dovetail guides, hardened, adjustable
- 3 automatic drill feeds
- Manual coarse feed for quill, with change-over for manual fine feed
- Quill with automatic micrometer depth stop
- Reversing switch for forward reverse rotation
- Central lubrication for spindle, nut and guides
- Manual spindle brakes
- Pneumatic tool clamping
- 3-axis position indicator, coolant system, and LED work lamp (included in standard equipment)

3-axis position indicator

- More accuracy
- Lower error rate
- Increased productivity
- Resulting in valuable time savings
- For increased productivity
- Easy to read display
- Operator-specific features
- Convenient keyboard layout
- Resolution: 0.01/ 0.005 mm
- Default coordinates
- Axis position is maintained when display is turned off
- Hole circle pattern calculation
- Calculator function
- Storage for 10 tools
- Radius / diameter toggle
- Mm/inch conversion
- Easy expansion and maintenance-free operation

PRODUCT.BROCHURE.STANDARD_EQUIPMENT

3-axis position indicator X.Pos 3.2
 Automatic table feed in X direction (TV 1000)
 Pneumatic tool clamping
 Coolant system
 Central lubrication
 Vertical guideway cover
 LED work lamp
 Operating tools
 Operator manual



KNUTH on YouTube

Information to the point

On our YouTube channel you can find videos for nearly all machines from our program. We show the machines from current deliveries and you get an impression of the handling, the processing quality and the machining performance.

**Are you interested in a machine for which you cannot find a current video?
Please feel free to contact us!**