

Conventional Vertical Milling Machines

Mark Super SV.M





M	RKI	NIC.	ΛВ	
VVO	LLI	.IVG	An	EA

TECHNICAL SPECS

Table dimensions	820 mm x 240 mm
Drilling capacity in steel	32 mm
Drilling capacity, cast iron	45 mm
Shaft milling	22 mm
Head elevation	350 mm
Number of table T-slots	3 positions
T-slot table (width x spacing)	14 mm x 65 mm

TRAVELS

Travel X-axis manual / autom.	450 mm
Travel Y-axis	150 mm

VERTICAL MILLING HEAD

Spindle mount	4 MT
Quill stroke	130 mm
Quill diameter	75 mm
Spindle nose-to-table distance	425 mm
Throat	245 mm
Head swivel range	90/70°
Speed	(12) 75-438/438-2500 1/min
	· ·

FEED

Quill feeds	0,12/0,18/0,25 mm/R			
DRIVE CAPACITY				
Main motor rating	1,5 kW			
MEASURES AND WEIGHTS				
Overall dimensions (length x width x height)	1.27 m x 0.97 m x 2.05 m			
Weight	320 kg			

SKU: 470596

TRIAL MACHINE

Without CE mark, only for export to countries outside the EU

The Mark Super series offers drill press/milling machines for a wide variety of applications. They are ideal compact drill presses with powerful drive and wide speed range. And they also are perfect milling machines for machining steel and non-ferrous metals. Ideally suited for workshops and maintenance shops for single part machining, small batch productions, and training applications.

- Feed on the X axis
- Automatic drill feed
- Digital depth indicator for quill
- Thread cutting unit
- Swiveling cutter head
- Infinitely variable spindle speed
- Coolant system integrated in base
- 3-axis position indicator, fully assembled











Integrated coolant system

PRODUCT DETAILS

Machine Frame

- Mark Super series machines are compact and user-friendly drill press/milling machines for workshop and training applications
- The machine frame is made of cast-iron and features wide, precisely adjustable dovetail guides on all axes
- The convenient base ensures maximum stability and also offers storage space
- The work table features a large clamping area and an infinitely variable feed motor on the X axis
- The TV 1000 is specifically configured for use on the Mark Super, and the high-torque drive ensures a consistent and efficient milling operation
- · A rapid feed simplifies machine setup and shortens downtime during machining

Cutter head

- The cutter head features motorized vertical positioning and swivels 45° to the left and right
- The swiveling cutter head allows drilling and milling at various angles
- A two-step main spindle motor and the gears with oil bath lubrication provide a wide speed range
- For drilling jobs, the quill can be fed manually or via the automatic drive
- The high-precision quill micro-feed can also be operated via an auxiliary hand-wheel
- The integrated feed gear transmission provides three gear steps are available for the automatic guill feed
- An adjustable stop gauge automatically stops the feed upon reaching the desired depth
- The exact quill stroke is displayed on a digital depth indicator
- Additionally, the machine features a tapping feature with automatic spindle reversal upon reaching the preset thread depth
- High-quality electric components ensure reliable operation and maximum availability

The Mark Super SV.M provides more power with infinitely variable speed control for an even wider range of applications

- 2 gear steps and a DELTA variable frequency drive ensure high torque across the entire speed range for powerful machining
- The selected spindle speed is displayed directly on the control panel
- High-quality electric components ensure reliable operation and maximum availability

Equipment

- The newest generation of our standard position indicators completes this machine's professional equipment package
- The delicate glass scales are mounted within robust safety guards, which also protect against chips and coolant
- An integrated coolant system is part of the standard equipment package

Sample product

- Only for markets outside the EU. Fully tested and fully functional machine, no warranty, but includes a 6-month warranty on replacement parts (wear parts excluded)
- For the EU market, we offer a wide portfolio of drill presses. Please visit our website for detailed information
- If you have questions regarding a product or sales limitations, please contact our sales experts

Standard Equipment

- 3-axis position indicator
- Automatic quill feed
- Base
- TV 1000 table feed
- Drill chuck diameter 13 mm
- Tool-holder bits
- Coolant system
- Operation manual