

Guillotine Shears

Prestige RGM 2003



SKU: 470609 TRIAL MACHINE

The Prestige RGM series features a solid construction and is of high quality. These modern plate shears are equipped with a powerful drive motor, and a straight cutter angle ensures minimum workpiece torsion during cutting. The back gauge is positioned manually

- Solid steel weldment with sliding block guide
- Manual back gauge with travel display
- Work area secured by light curtain

TECHNICAL SPECS

WORKING AREA

| Working length | 2050 mm |
|------------------------|-------------|
| Cutting angle | 1.9 deg |
| Work table height | 800 mm |
| Work table depth | 430 mm |
| Number of support arms | 3 positions |
| Support arms | 430 mm |
| Strokes per minute | 34 H/min |
| | |

BACK GAUGE

CUTTING CAPACITIES

Plate thickness (max.) - 3 mm - 3 mm 450 N/mm²


DRIVE CAPACITY

Motor rating main drive 4 kW

MEASURES AND WEIGHTS

| Overall dimensions (length x width x height) | 2.65 m x 2 m x 1.25 m |
|--|-----------------------|
| Weight | 1800 kg |







PRODUCT DETAILS

Machine Frame and Drive System

- The machine frame is made of a very rigid, solid steel weldment and the cutter bar is sliding-block guided
- The high-precision guideway ensures clean cuts
- A rigid, continuous hold-down fixes the sheet metal plate right in front of the cut line

Material Support

- The rigid side angle stop simplifies precise alignment of the plate perpendicular to the cut line
- Rugged support arms ensure a strong hold of large plates
- A wide support table simplifies workpiece handling

Ergonomic Design

- The bright LED illumination of the cut line creates a clearly visible shadow on the marked line
- All lubrication points are easily accessible to simplify regular maintenance

Back Gauge

- The back gauge is positioned manually via a hand wheel
- A scale on the back gauge simplifies exact positioning
- The easy accessible work area at the back gauge is secured by light curtain

Equipment

- High-quality electric components ensure reliable operation and maximum availability
- The mobile foot switch gives the operator added flexibility and both hands are free for handling the workpiece

Standard Equipment

- 750 mm manual back gauge system
- Cut-line lighting
- Finger guard
- Light curtain
- Foot switch with emergency stop switch
- Lateral stop with scale and T-slots
- Support arms

The machine has been tested and is fully functional.