

# Column Drilling Machines **KSS 25V**





# **TECHNICAL SPECS**

#### WORKING AREA

Drilling capacity	25 mm
Column diameter	102 mm
Quill stroke	130 mm
Throat	230 mm
Spindle nose-to-table surface distance	680 mm
Spindle nose-to-foot distance	965 mm
Foot set up area (length x width)	330 mm
Table set up area	330 mm x 380 mm

#### HEADSTOCK

Spindle mount	3 MT
Spindle speed	230 1/min - 2160 1/min

#### DRIVE CAPACITY

Motor rating main drive 1.5 kW

#### **MEASURES AND WEIGHTS**

Height	1580 mm
Weight	190 kg

## SKU : 765502 USED

This series of table and column drilling machines is ideal for light drilling work in steel, cast iron and non-ferrous metals. They are used in workshops and industry for repairs and individual production.

- Universal use
- Compact and powerful
- Robust
- Low maintenance and quiet operation

### **PRODUCT DETAILS**

- Automatic feed

- Automatic feed
  Coolant system
  Belt drive for low-noise operation, low-maintenance and robust design
  Precision spindle bearing long life and high accuracy
  Table movement via hand-crank and gear rack
  Adjustable depth stop at the capstan handle
  Long quill stroke with precision guide
  Thick-walled column for maximum rigidity during machining of large parts